

LIGHT-DUTY ANCHORS





LIGHT-DUTY ANCHORS

Ramset[™] has a full range of high-quality, light-duty anchors to suit your fixing needs. For further technical information, please email sales@itwcpsea.com.

Hit M



A high-quality, excellent performance polyamide lightweight anchor with ETA approval that is easy and quick to set. The "M" design improves the expansion in all kinds of materials such as concrete, solid block, stone, solid brick, aerated concrete, plasterboard, dry partition walls, hollow block wall, hollow brick and hollow floor beam.

APPLICATIONS:

Façade insulations, claddings, trunks & cable rails, doors and window frames, skirting, electrical shutter rails, roof flashings, water heater collars

Pro 6



A high-performance, hollow base material nylon anchor with unique, six expandable zones for effective anti-rotation in most base materials. Fasten into concrete, solid block, solid stone, solid brick, hollow block, aerated concrete, hollow slab and hollow brick.

APPLICATIONS:

Kitchen fittings, Bathroom fittings, Electrical accessories installations, picture fittings

Ramset Nylon Anchor



The Ramset Nylon Anchor is a removable light duty, impact/rotation setting, interference fit anchor, with a variety of head styles, designed for use in a variety of substrates such as concrete, stone, solid brick, solid block, grout filled block and hollow block.

APPLICATIONS:


Electrical Fitting Installation, Sign Installation, Pipe/Conduit Saddle Installation

Hollow Wall Anchor



The Ramset Hollow Wall Anchor is an all metal, light duty, cavity fixing for plasterboard and other hollow wall materials up to 38mm. It is designed for use in plasterboard, plywood or cement sheet

APPLICATIONS:





Driva - Plasterboard Anchor (Self-drilling)



The Ramset Driva is designed for quick and easy installation for light to medium loads. Installation is done using a screwdriver. It may be used for aerated concrete by drilling an 8mm hole. Available in flat, countersunk, and screw head

ADDI ICATIONS

Bathroom Accessories, Mirrors, Fastening Components on the Wall

Driva Plus - Plasterboard Anchor (Self-drilling)



The Ramset Driva Plus is a self-drilling plasterboard anchor with a swivel hinge system for heavier loads.

APPLICATIONS:

Bathroom Accessories, Mirrors, Fastening Components on the Wall



Ramset Plastic Plug



Ramset plastic plugs are traditional expansion plugs for light-duty anchoring in concrete, stone, solid brick and solid block.

APPLICATIONS:

Light Hook Installation, Light Bracket Installation, Electrical Fitting Installation, Bathroom Accessory Installation, Pipe/Conduit Saddle Installation, Sign Installation

Ramset Nylon Toggle



The Ramset Nylon Toggle is a one piece, light-duty nylon cavity fastener for fixing into plasterboard. It has anti-rotation fins that prevent spinning in the hole when the screw is being installed. The low profile head allows for flush fixing.

APPLICATIONS:

Light Hook Installation, Light Bracket Installation, Electrical Fitting Installation, Bathroom Accessory Installation

HIT M Hammer-In Anchors



Part No.	Description	Min Base Thickness (mm)	Max Fixture Thickness (mm)	Overall Anchor Length (mm)	Anchor/ Hole Ø (mm)	Min Hole Depth (mm)	Order Qty
7C-HITM-5052-7P	HITM 5-5/27 P Head Version	60	5	27	5	30	200
7C-HITM-5153-7P	HITM 5-15/37 P Head Version	60	15	37	5	30	200
7C-HITM-6053-2P	HITM 6-5/32 P Head Version	65	5	32	6	35	200
7C-HITM-6123-9P	HITM 6-12/39 P Head Version*	65	12	39	6	35	100
7C-HITM-6255-2P	HITM 6-25/52 P Head Version*	65	25	52	6	35	100
7C-HITM-6406-7P	HITM 6-40/67 P Head Version*	65	40	67	6	35	100
7C-HITM-8104-2P	HITM 8-10/42 P Head Version	65	10	42	8	40	100
7C-HITM-8306-2P	HITM 8-30/62 P Head Version*	65	30	62	8	40	100
7C-HITM-8609-2P	HITM 8-60/92 P Head Version*	65	60	92	8	40	100
7C-HTM8-8011-2P	HITM 8-80/112 P Head Version*	65	80	112	8	40	100
7C-HTM8-1H13-2P	HITM 8-100/132 P Head Version*	65	100	132	8	40	100
7D-HTM6-0532-SS	HITM 6-5/32 P A2	65	5	32	6	35	200
7D-HTM6-2552-SS	HITM 6-25/52 P A2	65	25	52	6	35	100
7D-HTM6-4067-SS	HITM 6-40/67 P A2	65	40	67	6	35	100
7D-HTM8-1042-SS	HITM 8-10/42 P A2	65	10	42	8	40	100
7D-HTM8-3062-SS	HITM 8-30/62 P A2	65	30	62	8	40	100
7D-HTM8-6092-SS	HITM 8-60/92 P A2	65	60	92	8	40	100
7D-HTM8-1H13-SS	HITM 8-100/132 P A2	65	100	132	8	40	100

PRO 6 Universal Anchor



Part No.	Description	Screw Ø (mm)	Overall Anchor Length (mm)	Anchor/ Hole Ø (mm)	Min Hole Depth (mm)	Order Qty
7C-PR06-0525	PR06 5x25	3 - 4	25	5	35	100
7c-PR06-0630	PR06 6x30	4 - 5	30	6	40	100
7C-PR06-0840	PR06 8x40	4.5 - 6	40	8	50	50
7C-PR06-1050	PR06 10x50	6 - 8	50	10	65	25

Hollow Wall Anchor



Part No.	Description	Wall Thickness (mm)	Max Fixture Thickness (mm)	Drilled Hole Ø (mm)	Order Qty
7C-HW10-M4PV	Hollow Wall Anchor M4 10 Pointed	6 - 10	15	8	100
7C-HW10-M4VV	Hollow Wall Anchor M4 10	6 - 10	17	8	100
7C-HW13-M4VV	Hollow Wall Anchor M4 13	8 - 13	15	8	100
7C-HW24-M4VV	Hollow Wall Anchor M4 24	16 - 24	17	8	100
7C-HW38-M4VV	Hollow Wall Anchor M4 38	34 - 38	15	8	100
7C-HW14-M5VV	Hollow Wall Anchor M5 14	8 - 13	20	9	100
7C-HW16-M6VV	Hollow Wall Anchor M6 16	6 - 16	22	13	100
7C-RABB	Setting Tool Hollow Wall Anchor				1

LIGHT-DUTY ANCHORS

Driva™



Part No.	Description	Screw Ø (mm)	Max Fixture Thickness (mm)	Screw Length (mm)	Order Qty
7C-DRVA-TP12	Driva TP12 Flat Head	4.5	12	5	100
7C-DRVA-TF27	Driva TF27 Countersunk Head	4.5	27	50	100
7C-DRVA-TF05	Driva TF5 Countersunk Head	4.5	5	25	100
7C-DRVA-THR	Driva C7 Screw Stud	4.5	5	37	100

Driva™ Plus



Part No.	Description	Screw Ø (mm)	Max Fixture Thickness (mm)	Screw Length (mm)	Anchor Length (mm)	Order Qty
7C-DRPL-TP12	DrivaPlus TP12 Flat Head	4.5	12	45	39	100
7C-DRPL-TP30	DrivaPlus TF30 Countersunk Head	4.5	30	60	39	100

Ramset[™] Nylon Anchor



Part No.	Description	Screw Ø (mm)	Overall Anchor Length (mm)	Anchor/ Hole Ø (mm)	Min Hole Depth (mm)	Order Qty
7C-ED05-033V	Nylon Anchor 5 x 33	3	33	5	40	100

Ramset™ Plastic Plug



Part No.	Description	Hole Ø (mm)	Plug Length (mm)	Screw Gauge	Order Qty
7C-RABB	Green Plastic Plug	6.5	30	10 - 12	100

Ramset[™] Nylon Toggle - Nylon Cavity Fastener



Part No.	Description	Hole	Screw Gauge	Wall	Order Qty
		Ø (mm)		Thickness (mm)	
7C-RTOG-13W	Plastic Toggle 13mm	8	6 - 8	9-13mm	100

Distributor's Stamp



ITW Construction Products (SEA) Pte. Ltd.

4 Changi South Lane, #06-01 Nan Wah Building, Singapore 486127 Tel: (+65) 6746 1177 Fax: (+65) 6746 1482 Email: sales@itwcpsea.com Website: www.itwcpsea.com

Brochure Reference Number: ITW11-LDA01